

PUFAS Adhesive for Borders BK direct

PUFAS Bordüren-Kleber BK direkt

- for all paper, vinyl and non-woven borders
- supplied with brush for straight-forward, neat application
- very high bond strength
- dries to transparent finish

Instructions for use:

PUFAS Adhesive for Borders BK direct is ideally suited for pasting borders made from paper, textile and vinyl onto wallpapers, wall coverings, emulsion paints and all mineral surfaces such as plaster, concrete and masonry.

Technical specifications:

Components: synthetic resin dispersion
Density: approx. 1.1 g/cm³
pH-value: approx. 7-8
Usage: the tube contents suffice for approx. 10 m borders (15 cm wide)

Substrate preparation:

The surface must be dry, firm, and free of release agents (dust, formwork oil, etc.). The existing wallpapers must adhere well to the surface.

Application:

Moisten the backs of the cut borders with water. After approx. 4-5 minutes apply PUFAS Adhesive for Borders BK direct. Fold the borders together, roll up and paste onto the surface after the recommended softening time. Always following the instructions for use of the border manufacturer.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the surface and/or room temperature are below + 5° Celsius.

Immediately remove any adhesive residues with water or a damp cloth.

Clean brushes in water immediately after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool place. Keep the containers tightly sealed.

Available sizes:

250 g 4007954012062 001206000 REG

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.