

PUFAS Fast-setting Cement BZ

PUFAS Blitzzement BZ

- Rapid-set fixing mortar
- For indoor and outdoor use
- Weather-resistant
- High compressive strength
- Corrosion-inhibiting
- rapid-set
- 3- to 5-minute working life
- Low in chromates according to EC-Regulation No 1907 /2006, Annex XVII (47)

Instructions for use:

PUFAS Fast-setting Cement BZ is ideally suited for fixing and anchoring construction elements (e.g. hinges, shelf holders, rawl plugs, railings) and for quickly making good holes and cracks in mineral surfaces, e.g. lime, cement and gypsum plaster, concrete, air-entrained concrete, clay tiles, etc.

PUFAS Fast-setting Cement BZ cannot be used on surfaces made from wood, metal and plastic and coats of emulsion paint.

Technical specifications:

Components:	special cement mixture, fillers, additives
pH-value:	approx. 12
Apparent weight:	approx. 1.35g/cm ³
Mix ratio:	100 g powder in 25 ml water
Working time:	3-5 minutes at 20° Celsius
Bending tensile strength:	approx. 4.9 N/mm ²
Compressive strength:	approx. 17 N/mm ²

Substrate preparation:

The surface must be firm and free of release agents (dust, formwork oil, etc.). Pre-treat highly absorbent, sanding and chalking surfaces with PUFAS Deeply-Penetrating Primer LF – solvent free.

Application:

Pour clean, cold water into a clean container and sprinkle in PUFAS Fast-setting Cement BZ. Immediately mix vigorously, until a smooth, lump-free mortar results.

Immediately apply the mixed compound to the area to be repaired using a stopping knife and smooth the surface. Fixed construction elements can be loaded after 24 hours.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a dry place! Keep the containers tightly sealed!

Available sizes:

1 kg	4007954038017	003801000	REG
5 kg	4007954038024	003802000	REG