

## PUFAS Assembly Adhesive FIX PUFAS Montage-Kraftkleber FIX

- for skirtings, mouldings, ceramic wall tiles and similar materials
- high strength
- reliable initial adhesion
- evens out slight irregularities
- solvent-free
- for indoor and outdoor use

### Instructions for use:

PUFAS Assembly Adhesive FIX is ideally suited for gluing baseboards, wood panels, décor and insulating panels made of polystyrene, decorative beading, ceramic tiles, mosaics, etc.

Not suitable for gluing polyethylene and polypropylene

### Technical specifications:

Components: copolymer plastic emulsion, fillers  
Density: approx. 1.61 g/cm<sup>3</sup>  
pH-value: approx. 8  
Usage: approx. 300-500 g/m<sup>2</sup> depending on the surface property

### Substrate preparation:

The surface must be dry, firm and free of release agents (grease, dust, etc.) Sanding and chalking surfaces must be pretreated with PUFAS Deeply-Penetrating Primer LF – solvent free. If the material to be glued cannot absorb moisture, the surface must be absorbent.

### Application:

Apply PUFAS Assembly Adhesive FIX in spots or strips to the parts to be assembled and push together. Heavy parts must be fixed in place until the adhesive has set.

Remove residual adhesive immediately with water.

### Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the surface and/or room temperature are below + 5° Celsius!

Clean tools in water after use.

### Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

### Storage:

Store in a cool but frost-free place.

### Available sizes:

400 g	4007954072011	007201000	REG
400 g	4007954072929	007211092	CIS

### Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.