

PUFAS Silicate-Fixative SF

Use:

Stabilized, potassium-silicate-based water glass primer for concrete, lime and cement render, masonry, gypsum substrates, cement fibreboard and existing lime, mineral or silicate paint finishes. Stabilizes substrate and regulates suction. Dries to transparent finish.

Properties:

- primer for mineral substrates
- for thinning silicate and silicate emulsion paints
- stabilizes substrate and regulates suction
- highly water vapour-permeable
- exhibits natural properties to protect against mould
- for indoor and outdoor use
- preservative-free

Technical data:

Raw material base:	Potassium water glass, polymer dispersion and additives
Density:	Approx. 1.1 g/cm ³
pH value:	Approx. 11
GISCODE for coating materials:	BSW10
Colour:	Whitish

Substrate preparation:

Substrate shall be dry, clean and free from adhesion-impairing substances. Remove non-firmly adhering components and laitance.

Application:

Shake canister prior to use and brush apply in undiluted form or, depending on substrate, diluted up to 1:2 with water. Pretreat very highly absorbent substrates with two wet-on-wet primer coats, working in material with brush.

Consumption:

Approx. 100 ml/m² for single coat, depending on substrate. Exact consumption rate to be determined by trial application on site.

Safety at work:

Avoid contact with skin and eyes. Wear safety gloves and goggles (not with glass). In case of contact with skin, rinse immediately with plenty of water. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice if necessary.

Note:

Do not use at building fabric and room temperatures below + 5 °C. Mask areas not to be treated with sheeting. Avoid splashes on glass, aluminium, ceramics, marble and similar materials. Immediately remove accidental splashes with water. Do not mix with paints with any other material base (e.g. emulsion paints). Wash tools with water immediately after use.

Please consult safety data sheet for safety-relevant data. Up-to-date safety data sheets are available from our website at www.pufas.de or from sds@pufas.de.

Storage:

Store in cool, though frost-free environment in properly sealed containers. Keep out of reach of children.

Disposal:

Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling. Dried material residue may be disposed of as domestic or construction site waste. Dispose of product waste under EWC waste code 08 01 12.

Item No.	EAN	Container size
065801000	4007954658017	1 ltr
065803000	4007954658031	5 ltr



Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.