

## PUFAS Algae and Mould STOP Concentrate

### PUFAS Algen und Schimmel STOPP Konzentrat

- dilutable 1:10 with water
- chlorine-free and odourless
- for cleaning facades, roofs, paving stones, patios, fences etc.
- removes mould, algae and green growth, also indoors, without unpleasant odour emissions
- ideal for clay brick, stone, concrete etc.
- suitable as pretreatment for coatings and facade impregnations
- self-acting and preventive
- excellently suited for application with pressure spray equipment

#### Instructions for use:

Removes mould, algae and moss in interior areas – for example in sanitary installations. Cleans house walls, floors, roofs, garages, wood, tiles, clay tiles, stone, and concrete, etc. Can also be used as a cleaning surface pre-treatment for subsequent coats and facade impregnations.

#### Technical specifications:

Components: Didecyl dimethyl ammonium chloride

Density: approx. 1 g/cm<sup>3</sup>

pH-value: approx. 8

#### Application:

Dilute Pufas Algae and Mould STOP Concentrate with water in a ratio of 1:10. Apply the renovating solution using a brush or spray on using a suitable spray gun and leave to take effect. This occurs within 1 - 3 days. In case of severe contaminations, if no optical change appears in the treated surface, apply a further coat of Pufas STOP Algae and Mould STOP Concentrate.

#### Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Wash off any residues using clean water.

#### Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

#### Storage:

Store in cool, though frost-free environment in properly sealed containers. Keep out of reach of children.

#### Available sizes:

1 l	4007954076026	007602000	REG
2.5 l	4007954076019	007601000	REG

#### Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.