

PUFAMIX Universal Concentrated Colorants

PUFAMIX Universal-Abtönkonzentrate

- extremely strong colour and economical
- 28 brilliant colour shades
- for tinting almost all materials
- excellent mixing performance
- very good light resistance
- frost resistant
- space saving due to small volume
- all LW (light and weather resistant) oxide types are suitable for aromatic-free lacquer systems and silicate paints (Colour shades No. 3, 4, 5, 14, 19, 20, 21, 22, 23, 24, 25)

Instructions for use:

PufaMIX Universal concentrated colorants are ideally suited for tinting standard commercial, diluted emulsion, binder, and latex paints, synthetic resin plasters, acrylic varnishes, alkyd resin varnishes, nitrocellulose lacquers and similar paint systems. Furthermore, they are suitable for tinting scumble coats, wood stainers, wood waxes and cement paints.

The shades denoted with "L" in the colour card (No. 6, 7, 10, 18) are only for indoor use, those denoted with "LW" are for both indoor and outdoor use.

Only the oxide colours (No. 3, 4, 5, 14, 19, 20, 21, 22, 23, 24, 29, 30, 31, 32) can be used for tinting silicate paints for outdoor use and low-aromatic compound and aromatic-free paints.

Technical specifications:

Components: Inorganic and organic pigments, dispersed in water and propylene glycol

Density: approx. 1.22 g/cm³

pH-value: approx. 6.5-7.5

Application:

Shake the bottle well before use.

Add PufaMIX Universal concentrated colorants to the paint to be tinted and mix thoroughly until fully homogeneous. We recommend using a stirring machine when tinting varnishes. The basic rule is: Always try out first and carry out a rub off test! First tint – then thin!

The following maximum added quantities are to be observed for the various paint systems.

Emulsion paints max. 10 %

Acrylic varnishes max. 6 %

Alkyd resin varnishes max. 8 %

Synthetic resin plasters max. 10 %

Scumble coats max. 5 %

All PufaMIX Universal concentrated colorants can be mixed with each other.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Clean tools with water immediately after use

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool and frost-free place! Keep the containers tightly sealed!

Available Colours:

Available in 32 shades for water and solvent-based paint systems.

20 ml	07xx01000	REG
200 ml	07xx02000	REG
500 ml	07xx03000	REG