

PUFAS Effect Glazes

PUFAS Effektlasuren

- thixotropic wall glaze
- for wallpapers, emulsion paints, plasters, decorative elements made of polystyrene and similar interior surfaces
- solvent-free
- consumption: approx. 80–120 ml/m²

Instructions for use:

A glaze on acrylate basis with a modern brighter effect that change depending on the light. Suitable for ceilings and wall coatings on wallpapers, colours, brick, masonry, finery, Styrofoam and similar interior surfaces. The acrylic gets transparent after drying and only the glitter remains visible.

Technical specifications:

Components: Styrol-Acrylic- Dispersion, effect pigments, additive
 Density: approx. 1.05 g/cm³
 pH-value: approx. 8 – 8.5
 Usage: 80 - 120 ml/m²

Substrate preparation:

The surface must be dry, firm and free of release agents (dust, formwork release oil, etc.).

Do not apply PUFAS Effect Glaze until the wallpaper has completely dried.

Application:

Shake well before use!

Pufas Effect Glaze is ready to use and can be applied using a paint roller, brush or spreader.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the surface and/or room temperature are below + 5° C.

Clean tools in water immediately after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool, but frost-free place. Keep the containers tightly sealed.

Available sizes:

Pearl Effect:
 750 ml 4007955170020 017002001 REG
 1.5 l 4007955170037 017003001 REG

Brilliant Effect:
 750 ml 4007955171027 017102001 REG
 1.5 l 4007955171034 017103001 REG

Diamond Effect:
 750 ml 4007955173021 017302001 REG
 1.5 l 4007955173038 017303001 REG

Rubin Effect:
 750 ml 4007955172024 017202001 REG

Saphir Effect:
 750 ml 4007955174028 017402001 REG

Smaragd Effect:
 750 ml 4007955175025 017502001 REG