

Special Paint for tile, bathtub, kitchen

Use:

Professional renovation system for coating wall tiles, enamelled-steel bathtubs, shower trays and washbasins, and plastics kitchen fronts.

Properties:

- special paint for tiles, bathtubs and kitchens
- finishing coat and sealer in single coat
- gloss finish
- extremely durable and easy to clean
- solvent-free and low-odour
- opaque white finish
- colour: pure white
- base set for approx. 2.8 m² comprising
 - 1 pot of Special Paint
 - 1 bottle of hardener
 - 4 sheets of sandpaper (P120 and P320)
 - 1 paint tray
 - 1 pro flat brush
 - 1 pro paint roller with arm
 - 1 wooden stirrer
 - 1 tack cloth

Technical data:

Raw material base: Synthetic resin, fillers, pigment and additives
 Density: Approx. 1.5 g/cm³

Substrate preparation:

The following ancillary products, not included in set, are needed for each application, depending on nature of surface to be coated:

- **for coating tiles**
 1. Tile & Joint Cleaner
 2. Alkaline Cleaning and Degreasing Agent
- **for coating enamelled-steel bathtubs etc.**
Alkaline Cleaning and Degreasing Agent
- **for coating plastics furniture fronts**
Alkaline Cleaning and Degreasing Agent
- Also use Silicone Remover, for example, where necessary

Tinting:

For colour finishes to tiles or kitchen fronts, Special Paint can be tinted with indicated PUFAMIX or decoMIX Universal Concentrated Colorants. Do not tint Special Paint for coating bathtubs and shower trays.

6	5	19	21	18	4	10	24	13	9	
Maisgelb	Oxyd-Ocker	Kamel	Terra-braun	Orange	Oxyd-Rot	Rot	Stein-grau	Grasgrün	Blau	2 %
										1 %
										0,2 %
L-Type	LW-Oxyd-Type	LW-Oxyd-Type	LW-Oxyd-Type	L-Type	LW-Oxyd-Type	L-Type	LW-Oxyd-Type	LW-Type	LW-Type	

Application:

1. Pretreat surface as instructed
 2. Mix Special Paint and hardener
 3. Brush apply Special Paint
 4. Spread Special Paint with roller
- Detailed application guidelines included in pack.

Note:

Not suitable for coating floor tiles, acrylic bathtubs/shower trays and worktops. Substrates with special dirt-repellent properties (e.g. "lotus effect") are not suitable for renovation coating. Do not use Special Paint and hardener separately. Do not use at temperatures below +5 °C. Wash tools with water after use.

Please consult safety data sheet for safety-relevant data. Up-to-date safety data sheets are available from our website at www.pufas.de/www.decotric.de or from sds@pufas.de/sds@decotric.de.

Storage:

Store in cool, though frost-free environment in properly sealed containers. Keep out of reach of children.

Disposal:

Hand over only fully emptied containers for recycling. Dried material residue may be disposed of as domestic or construction site waste. Dispose of uncured waste under EWC waste code: 08 04 11. Do not allow to enter drains, sewers, surface waters or ground.

Item No.	EAN	Container size
025001000	4007954250013	set



Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.