

PUFAS Anti-Graffiti Permanent AGP

PUFAS Anti-Graffiti Permanent AGP

- long-term protection
- UV-stable and non-yellowing
- glossy and intensifies the colours
- Easy cleaning with cold water
- durable, elastic protective film
- resistant to weathering and ageing
- 1 l for approx 4-5 sqm for two layers

Instructions for use:

For all mineral substrates, e.g. concrete, clay bricks/blocks, natural stone and other sandstone. Other substrates (e.g. metals, plastics and paint) require pre-treatment with Anti-Graffiti Primer AGG.

Technical specifications:

Components: Aliphatic hydrocarbons and additives
 Density: approx. 0.9 g/cm³
 Dilution: Material supplied ready-for-use
 Usage: Approx. 100 – 130 ml/m² per coat, depending on substrate and application method. Exact consumption rates are to be determined by trial application on site
 Drying time: Approx. 24 hours (at 20 °C, 65 % relative humidity and moderately absorbent substrate). Higher humidities, lower temperatures or low substrate suction will lengthen drying time.

Substrate preparation:

Substrate shall be dry, clean and free from salts, efflorescence and adhesion-impairing substances (e.g. dust, grease). Repair cracks and holes with suitable filler. Substrates such as metals, plastics and paint require pretreatment with Anti-Graffiti Primer AGG. Ensure that new mineral plasterwork/rendering and surfaces treated with mineral mortars or fillers have adequately set and cured. Do not apply directly to extruded-polystyrene ETICS (external thermal insulation composite system) board or similar systems.

Application:

Mask areas and construction elements not to be coated. Stir Anti-Graffiti Permanent AGP well prior to use and apply in undiluted form with solvent-resistant roller, brush or suitable airless spray equipment. Apply in two wet-on-wet coats. Avoid runs and curtaining. Spread out surplus material with roller.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not apply at substrate or ambient temperatures below + 10 °C or above + 30 °C.

Wash tools with water immediately after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Keep out of reach of children. Store in cool, though frost-free environment in properly sealed containers. Protect from direct sunshine.

Available sizes:

2.5 l	4007954070239	107003000	REG
-------	---------------	-----------	-----