

PUFAS Easy-Fill PUFAS Instant-Spachtel

Ready for use, weather resistant synthetic filler compound for use indoors and outdoors.

Instructions for use:	<i>PUFAS Easy-Fill</i> is ideally suited for improving, smoothing and coating uneven, rough ceilings, walls and facades as well as for reliable, widespread filling and smoothing of prefabricated concrete elements, lime, cement and gypsum based plasters. Can also be used on all mineral surfaces (concrete, air-entrained concrete, clay tiles, etc.) as well as emulsion paints and gypsum boards. Not suitable for filling works on wood, metal, glass and plastic.	
Technical specifications:	Components:	styrene-acrylate emulsion, fillers and additives
	Density:	1.70 g/cm ³
	pH-value:	8-9
	Usage:	approx. 1.7 kg/m ² for a 1 mm coat thickness
Surface preparation:	Prime highly absorbent, sanding and chalking surfaces with <i>PUFAS Deeply-Penetrating Primer – solvent free</i> . The surface must be dry, firm and free of dust and grease. Remove old, peeling wallpapers and distemper paints using <i>PUFAS Wallpaper Remover Tap-Ex</i> . Make good cracks and holes using <i>PUFAS Fill-Finish</i> or <i>PUFAMUR Super Bonding Filler</i> or outdoors with <i>PUFAMUR Exterior Façade</i> or <i>PUFAS Exterior Filler</i> .	
Application:	Apply <i>PUFAS Easy-Fill</i> onto the surface up to a thickness of max. 5 mm using a smoothing trowel. Unevenness can be smoothed or felted over when moist. Do not apply subsequent coats of paint or adhesive until the filled area has completely dried. It is not necessary to prime the surface for subsequent wallpapering and painting works. Do not use if the surface and/or room temperature is less than +5° Celsius. Clean tools in water immediately after use.	
Storage:	Store in a cool but frost-free place! Keep the containers tightly sealed!	
Available sizes:	400 g PE tube	033306031

