

PUFAS G30 Adhesive for wallpaper pasting machine

Special formulation with thread forming technology.

5 kg bucket with 10 bags portioned in 500 g – for up to 700 sqm

Area of application Secure bonding for all kinds of woodchip, non-woven wallpapers with smooth back, rough non-wovens such as paper-backed wallpapers.

- Product characteristics:**
- special formula for an even adhesive distribution
 - very high initial adhesion
 - provides a good correctability of wallpaper
 - good adhesion on wall edges
 - very high moisture resistance
 - lime- and cement proof
 - easy measuring thanks to 500 g portioned bags

Technical Specification:

Raw material:	Methyl cellulose, synthetic resin, additives
Bulk Density:	0,48 g/cm ³
pH-Value:	Approx. 8
Consumption:	Approx.. 200 ml mixed adhesive per sqm (exact quantity for the application has to be determined through a test application)

Surface preparation: The surface must be dry, solid, firm and free of release agents (dust, grease, formwork oil and similar). Remove flaking coatings, old wallpaper and distemper completely. Repair holes, cracks and uneven spots with filler (e.g. *pufamur Super Bonding Filler SH45, pufamur LS 8*). Treat highly absorbent surfaces with a prime coat. In case a thin translucent wallpaper is used we recommend the application of *PUFAS Wallpaper Primer-White* prior to wallpapering to avoid visibility of colour differences on the surface.

Preparation: Add content of 500g bag to clean cold water while stirring thoroughly. Continue to stir for a short while. Repeat after 2-3 minutes. Wait for 15 minutes and stir well again.

For	Mixing ratio	Quantity of water per 500g bag	Coverage of a 500g bag
Pre-pasting	1 : 50	25 l	approx. 250 sqm
wallpaper pasting machine	1 : 30	15 l	approx. 70 sqm

Application: Apply the adhesive evenly in the required thickness to the back of the wallpaper. After appropriate soak time position the stripes of wallpaper joint to joint to the wall and press firmly avoiding the formation of bubbles.

Always follow the wallpaper manufacturer's instructions

PUFAS G30 was developed especially for the use with pasting machines and is not suitable for the application by roller and airless device. For these types of application we recommend the use of PUFAS Security Adhesive SK or PUFAS Glassfibre and Non-Woven Wallpaper Adhesive GK.