

PUFAS Wallpaper Seam Adhesive NK

PUFAS Nahtkleber für Tapeten NK

- for sticking down debonded wall-paper seams on all substrates
- high bond strength
- 20 tubes in retail display pack

Instructions for use:

PUFAS Wallpaper Seam Adhesive NK is suitable for re-pasting peeling (cracked) wallpaper joints on all surfaces.

Surface specifications:

Components: Vinyl acetate ethylene plastic emulsion
pH-value: approx. 4-5
Density: approx. 1.1 g/cm³

Substrate preparation:

The surface must be firm and free of dust

Application:

Apply PUFAS Wallpaper Seam Adhesive NK directly from the tube onto the wallpaper of surface, spread evenly and press the peeling wallpaper back into place.

Depending on the ambient temperature and surface the drying time is approx. 10-15 minutes.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the surface and/or room temperature are below + 5° Celsius! Clean tools in water after use.

Immediately remove residual adhesive using a damp cloth.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool, but frost-free place! Keep the tube firmly closed!

Available sizes:

60 g	4007954074015	001801000	REG
60 g	4007954018118	001801098	EE

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.