

PUFAS renovation fleece adhesive RS plus

Area of application:

High-quality dispersion adhesive for the secure and permanent bonding of renovation, reinforcement, mineral and cellulose fleece as well as similar wall coverings.

Properties:

- Ideal for wallpapering machines and airless spray application
- for renovation, reinforcing, mineral and cellulose non-wovens
- reliable and durable bonding
- synthetic resin-reinforced
- ready-to-use formulation
- for pasting machines, roller and spray application
- very high moisture resistance when overcoating
- low spray fog formation when airless-spray applied

Technical data:

Raw material base:	Plastic dispersion, cellulose ether, additives
Density:	approx. 1.0 g/cm ³
ph-value:	approx. 10.5

Substrate

The substrate must be dry, sound, level and free of release agents (formwork oil, grease, dust, etc.). Remove old wallpaper with PUFAS wallpaper remover. Repair cracks, holes and uneven areas with a suitable PUFAS filler. Pre-treat highly absorbent, sandy or chalky substrates and sanded surfaces with PUFAS Hydrosol Tiefgrund LF.

Application:

Application to the wall covering: Apply the adhesive evenly to the back of the wall covering using a wallpapering tool and stick it in accordance with the manufacturer's instructions.

Application to the substrate: Apply the adhesive to the substrate in strips using a suitable airless device or a short-pile lambskin roller. Place the fleece in the fresh adhesive bed and press down evenly and bubble-free with a roller (foam rubber roller) or a wallpaper squeegee.

Consumption:

Approx. 150-250 g/m², depending on the substrate. Determine the exact consumption by applying a sample to the object.

Notes

Remove adhesive residues immediately with a damp cloth. Clean tools with water immediately after use.

Please refer to the safety data sheet for safety-related information. Current safety data sheets are available on our website www.pufas.de or at sds@pufas.de.

Storage

Store containers tightly closed and in a cool place, but not exposed to frost. Keep out of reach of children.

Disposal

Only recycle containers that are completely empty. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of product residues in accordance with EWC waste code no. 08 04 14.

Item no.	EAN	Container size
015803000	4007954158036	16 kg



Note

All information and data in this information sheet correspond to our practical experience and laboratory tests and are based on the current state of technology. However, they can only provide general information and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal liability can be derived from this information. It is the responsibility of the user to check the products for their suitability for the intended use under the respective conditions.