

PUFAS All-Purpose Wallpaper Adhesive

PUFAS Fertig-Kleister KF Spezial

- special adhesive for pasting machines and brush application
- corresponding to 1:20 mixing ratio
- with methyl cellulose
- high bond strength and moisture resistance easy to correct
- dries to transparent finish

Instructions for use:

PUFAS All-Purpose Wallpaper Adhesive is ideally suited for reliable, secure pasting of vinyl wallpapers, structured vinyl wallpapers, woodchip wallpapers, heavyweight paper wallpapers, embossed wallpapers, textile wallpapers and similar wall coverings. Ideally suited for use with standard commercial wallpapering machines.

Technical specifications:

Components: Cellulose ether, synthetic resin dispersion, additives
Density: approx. 1.0 g/cm³
pH-value: approx. 5.8
Usage: approx. 200-250 g/m²
Frost Resistance: to -20 °C

Substrate preparation:

The surface must be dry, firm and free of dust and grease. Remove old, peeling wallpapers and distemper paints using PUFAS Wallpaper Remover TL. Make good cracks and holes using PUFAS Interior filler FSI or PUFAMUR Super Bonding Filler SH45. Prime highly absorbent, sanding and chalking surfaces with PUFAS Deeply-Penetrating Primer LF – solvent free.

Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using PUFAS Iso-Plus 3in1 stain blocker spray. To make a subsequent change of wallpaper easier, we recommend priming the surface with PUFAS wallpaper primer – easy strip-off WG, especially when hanging washable wallpapers.

Application:

Apply the adhesive to the wallpaper using a wallpapering machine or brush, fold the fold the pasted ends inwards and hang after an adequate soaking time.

Always observe the wallpapering machine and wallpaper manufacturer's instructions for use.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the object and/or room temperature are below + 5° Celsius!

Clean tools in water after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool and dry place.

Store container well sealed!

If the product freezes, it is nevertheless usable after thawing.

Available sizes:

16 kg	4007954215036	021503000	REG
-------	---------------	-----------	-----