

PUFAS Wallpaper Remover TL

PUFAS Tapetenablöser TL

- concentrate
- · strong removing power
- for woodchip and other wallpapers
- rapid softening of wallpaper
- contains biodegradable surfactants

Instructions for use:

PUFAS Wallpaper Remover TL is suitable for easily removing paper, textile, vinyl and woodchip wallpapers as well as distemper paints

Technical specifications:

Components: non-ionic tensides (surfactants)

pH-value: approx. 7-8
Density: approx. 1.0 g/cm³

Usage: depending on the thinning, 250 ml suffice

for approx. 50-100 m²

Application:

To remove heavy wallpapers stir 250 ml PUFAS Wallpaper Remover TL in 10 l of water.

For lightweight wallpapers the amount of water added can be increased to 15 l.

Thin larger quantities with a corresponding ratio. Hot water increases the detaching effect.

Apply the solution, saturating the surface, using a brush or a suitable spray gun and leave for approx. 15 minutes to take effect. If necessary apply again. The softened wallpapers can then be easily pulled off. Roughen the surface of waterproof and painted wallpapers sing a needle roller or coarse abrasive paper before treating with remover.

To remove distemper paint, apply PUFAS Wallpaper Remover TL (dissolve 250 ml in 15 l of water) to the areas, leave to take effect for a short time and then scrape off using a stopping knife. Wash off any residues.

PUFAS Wallpaper Remover TL is neutral; stains can be easily removed with water. Subsequent pasting is not impaired.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the surface and/or room temperature are below + 5° Celsius! Clean tools in water after use.

Immediately remove residual adhesive using a damp cloth.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Keep containers tightly sealed and store in a cool but frostfree place!

Available sizes:

250 ml	4007954052044	005204000	REG
250 ml	4007954052143	005204031	EE
11	4007954052051	005205000	REG
5 I	4007954052037	005203000	REG