

PUFAS Wallpaper Protector TS PUFAS Tapetenschutz TS

- colourless
- transparent protective film for heavy-duty surfaces
- for wallpapers, emulsion paints, natural and cast stone masonry, maps and similar substrates
- dirt- and water-repellent
- solvent-free
- acrylate-based

Instructions for use:

PUFAS Wallpaper Protector TS is a colourless transparent, brushable, gloss coating for wallpapers, dispersion-based paints, plaster and similar substrates. For interior use. PUFAS Wallpaper Protector TS is not suitable for use on plastic, wood or metal.

Technical specifications:

Components: acrylate dispersion
pH-value: approx. 7-8
Density: approx. 1.0 g/cm³
Usage: 100-150 ml/m² per coating

Substrate preparation:

The surface must be dry, stable and free of dust, grease etc.

Application:

PUFAS Wallpaper Protector TS is ready for use and can be applied using a brush or a suitable spray application system.

The glossiness of the coating depends on the surface structure of the substrate.

For rough substrates, two coats are required to achieve an even, gloss coating. For silk lustre surfaces, *PUFAS Wallpaper Protector* can be diluted 1:1 with water.

PUFAS Wallpaper Protector TS can be used as a rendering base, diluted up to 1:4 with water depending on the absorbency of the substrate.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the surface and/or room temperature are below + 5° Celsius! Clean tools in water after use.

Immediately remove residual adhesive using a damp cloth.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool place, protect from frost! Ensure that the container is properly closed during storage!

Available sizes:

250 ml	4007954060063	006006000	REG
1 l	4007954060070	006007000	REG
5 l	4007954060032	006003000	REG