

Technical Data Sheet

PUFAS Wallpaper Base TR

PUFAS Tapetengrund transparent MIX

Area of application

Individually tintable, transparent base for intense colours – by adding up to 10% universal tinting concentrates or max. 20% full-tone and tinting paint, the wallpaper primer can be matched to the colour of the wall covering. Ideal for all wallpapering work – especially for dark or colour-intensive wallpapers and wall coverings. In a single step, the substrate is given the desired colour, uniform absorbency and a velvety-rough surface.

Properties:

- transparent, individually tintable base formulation for intensive colours
- special substrate preparation for dark and intensively coloured wallpapers and wall coverings
- creates uniformly absorbent substrates with good key
- does not seal off substrate

Technical data:

Raw material base:	synthetic resin dispersion, titaniumdioxide, mineral components transparent
Colour	approx. 1.5 g/cm ³ approx.
Density:	9
pH value	[BSW20
GISCODE for coating materials:	
EU VOC limit value for this product:	(Cat.: A/a, Wb)= 30 g/l (2010)
VOC content of this product:	max.: 1 g/l

Substrate preparation:

PUFAS Tapetengrund TR can be used on all mineral substrates (such as concrete, gypsum, lime and cement plaster, etc.), plasterboard, gypsum fibre, cement fibre and similar drywall panels, as well as on filled surfaces and similar substrates. Remove loose material, old wallpaper and poorly adhering paint. Prime highly absorbent, sandy and chalky substrates with PUFAS Tiefengrund LF. Repair cracks, holes and uneven areas – e.g. with pufamur Super-Haftspachtel SH 45 or pufamur Leichtspachtel LS 8.

Application:

Stir the wallpaper primer before use and apply to the substrate with a brush, roller or a suitable sprayer (max. grain size 0.2 mm). Once completely dry (approx. 6–8 hours, depending on the absorbency of the substrate, temperature and humidity), the painted surfaces can be wallpapered. Substrates already coated with wallpaper primer must not be treated with gypsum or cement-based fillers. For this purpose, we recommend pufamur Light Filler LS 8, Akkord Filler AS 5 or Finish Filler RAK 3.

Consumption:

Approx. 100-200 ml/m² – depending on the condition of the substrate. Determine the exact application quantity by testing on the object.

Storage:

Store containers tightly closed and in a cool place, but not exposed to frost. Keep out of reach of children.

Important information:

Do not use at object and room temperatures below +5 °C. Clean tools with water immediately after use. In case of contact with eyes, rinse immediately with water. Do not inhale spray mist during spray application.

Contains preservatives: benzisothiazolinone, methyl isothiazolinone. May cause allergic reactions. Advice for people allergic to isothiazolinone is available by calling 05541/7003-64.

Disposal:

Only recycle containers that have been completely emptied. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of liquid residues in accordance with waste code no. EWC 08 01 12. Do not allow to enter drains, water or soil.

Item no.:	EAN:	Filling:	Container size:
011901000	4007954119020	2.35 l bucket	2.5 l
011902000	4007954119006	4.7 litre bucket	5



Note

All information and data in this information sheet correspond to our practical experience and laboratory tests and are based on the current state of technology. However, they can only provide general information and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal liability can be derived from this information. It is the responsibility of the user to check the products for their suitability for the intended use under the respective conditions.