

PUFAS Bonding Plaster

PUFAS Haftputzgips

- single-coat wall and ceiling plaster for manual application
- for large-scale plastering of internal walls
- classed under mortar group P IVb
- easy to smooth
- reaction to fire: A1
- CE-compliant to EN 13279-1 (dry premixed gypsum plaster B4/20/2)

Instructions for use:

PUFAS Bonding Plaster is a one-layer wall and ceiling plaster (mortar class PIVb and is suitable for plastering all sable mineral surfaces. For interior use.

Technical specifications:

Components: natural gypsum, lime hydrate
pH-value: approx.. 12
Density: 500 – 650 kg/m³
Mixing ratio: 25 kg to 18 l water

Substrate preparation:

The surface must be dry, firm and free of release agents (dust, formwork release oil, etc.). Prime highly absorbent, sanding and chalking surfaces with PUFAS Deeply-Penetrating Primer LF – solvent free.

Application:

PUFAS Bonding Plaster into clean, cold water and stir vigorously. For larger amounts, use a motor agitator.

Apply the prepared mortar within 20 minutes, keeping to a minimum coat thickness of 5 mm. The central layer should be 10 mm.

After setting sets in, the surface can be smoothed or felled after slight wetting within a further 30-50 min.

When applying two layers, comb the first layer while still soft. Wait until thoroughly hard before applying the second layer.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Keep container tightly sealed and dry – preferably on a wooden grate

Available sizes:

25 kg 4007954036037 003603000 REG