

# PUFAMUR Exterior Façade Filler FS 30

## PUFAMUR außen Fassaden-Spachtel FS 30

Weatherproof, synthetic resin modified, cement-based joint filler for indoor and outdoor use.

**Instructions for use:** *PUFAMUR Exterior Façade Filler FS 30* is ideally suited for making good, smoothing, levelling and coating all mineral surfaces such as lime and cement based plaster, gypsum plaster, concrete, aerated concrete, clay tiles, etc. The filled areas are easy to smooth off and felt.

Not suitable for levelling out floors and for filling works on wood, metal, plastic, and glass or coats of emulsion paint.

**Technical specifications:**

Basic raw materials:	White cement, inorganic fillers, synthetic resin, additives
Bulk density:	approx. 1.25 g/cm <sup>3</sup>
pH-value:	12
Mix ratio:	2.25 parts by volume powder to 1 part by volume water (e.g. 1 kg powder in 350 ml water)
Consumption:	1.2 kg powder per m <sup>2</sup> with thickness of 1 mm
Working time:	approx. 30 minutes
Tensile bending strength:	4.0 N/mm <sup>2</sup> to EC 18555, T. 3
Compressive strength:	11.0 N/mm <sup>2</sup> to EC 18555, Part 3
Low in chromates according to EN 196-10	

**Preparation of surface:** The surface must be firm and free from release agents (dust, formwork oil, etc.) Remove flaking paints and loose plaster. Prime very smooth concrete as well as highly absorbent, sanding and chalking surfaces with *PUFAS Deeply-Penetrating Primer solvent free* or *LH Universal*.

**Instruction for use:** Pour clean, cold water into a container and sprinkle in *PUFAMUR Exterior Façade Filler FS 30*. Stir vigorously until a smooth, lump-free mortar results. Use the stirred joint filler within 30 minutes. Unevenness can be smoothed while moist or felted after approx. 90 minutes.

Do not apply subsequent coats and fixings until the treated surface has fully dried. Always observe the paint and adhesive manufacturer's instructions for the pre-treatment of cement bound surfaces (e.g. fluorinate with *OLAFIRN*).

Do not use if the surface and/or room temperature are below +5° Celsius. Clean tools in water immediately after use

**Important information:** Please see the EU Safety Data Sheet for all safety-related data (EU-CLP)

**Storage:** Store in a dry place! Keep the containers tightly sealed!

<b>Available sizes:</b>	5 kg paper bag	033904000
	25 kg paper sack	033906000

**Note:**

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.