

# pufamur Facade Repair FA5

## pufamur Fassaden-Fertigspachtel FA5

### Area of application:

pufamur Facade Repair FA5 is ideal for filling cracks and holes, levelling and smoothing facades, wall and ceiling surfaces, and embedding reinforcement tape. Can be used on all mineral substrates (e.g. concrete, masonry, fibre cement boards, gypsum, lime and cement plaster), emulsion and facade paints, synthetic resin plasters and similar surfaces.

### Properties:

- Fibre-reinforced for high strength
- Optimal substrate adhesion
- Easy to smooth
- Cures crack-free
- Application thickness up to 5 mm

### Technical data:

Raw material base: Plastic dispersion, mineral components, fibres and additives

Density: approx. 1.7 g/cm<sup>3</sup>  
pH value: 8 – 9

### Substrate

The substrate must be solid, dry, stable and free of separating agents (dust, form oil, etc.). Treat highly absorbent, sandy and chalky substrates with PUFAS *Hydrosol Primer Deep-Penetrating LF*. Fill deep holes and cracks with a suitable PUFAS filler.

### Application:

Stir before use. To repair cracks and holes, press the filler into the damaged area and smooth it out. For full-surface application, the filler can be applied in layers up to a maximum thickness of 5 mm. If a thicker layer is required, a second coat can be applied once the first coat has dried thoroughly.

### Consumption:

Approx. 1.7 kg/m<sup>2</sup> at 1 mm application thickness

### Notes

Do not process or dry at object and ambient temperatures below 5°C (+). Sand the filled surfaces within 1–3 days, depending on the ambient temperature and relative humidity. The sanding window may be shorter when using airless application.

Recommended sanding agent: Festol Garnet P 60 – 80  
Mirka Iridium Grit 60 – 80

Not suitable for full filling of the façade.

Please refer to the safety data sheet for safety-related information. Current safety data sheets are available on our website [www.pufas.de](http://www.pufas.de) or at [sds@pufas.de](mailto:sds@pufas.de).

### Storage:

Keep containers tightly closed and store in a cool place, but not exposed to frost. Keep out of reach of children.

### Disposal:

Only recycle containers that are completely empty. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of product residues in accordance with EWC waste code no. 08 04 10.

| Item no.  | EAN           | Container size |
|-----------|---------------|----------------|
| 072104000 | 4007954721049 | 8 kg           |
| 072105000 | 4007954721056 | 14 kg          |



### Note:

All information and data in this information sheet correspond to our practical experience and laboratory tests and are based on the current state of technology. However, they can only provide general information and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal liability can be derived from this information. It is the responsibility of the user to check the products for their suitability for the intended use under the respective conditions.