

pufamur Acrylic Fine Filler Rapid

pufamur Acryl-Feinspachtel rapid

Quick-drying, water-based repair filler

Area of application

Quick-drying, universal water-based repair filler. Can be used on all mineral substrates (such as gypsum, lime and cement plaster, concrete, etc.) and primed iron indoors and outdoors, as well as primed wood indoors. With rust inhibitor.

Properties:

- Quick-drying
- · Very easy to sand
- universal
- · Can be extended to zero
- no brush marks
- extra white
- · Can be painted over
- · Ready to use

Technical data:

Raw material base: Synthetic resin dispersion,

mineral components,

additives

Density approx. 1.9 g/m³

pH value:

GISCODE for

Coating materials: BSW 20

Substrate preparation:

The substrate must be dry, sound and free of release agents (dust, grease, etc.). Prime highly absorbent, sandy and chalky substrates with *PUFAS Hydrosol Primer Deep-Penetrating LF*. Wood and iron require priming with suitable products.

Application:

pufamur Acrylic Fine Filler is easy to apply and can be applied in several coats within a short period of time if necessary. After approx. 1–2 hours (depending on the coat thickness, substrate and ambient conditions), the filler can be sanded excellently. Once completely dry, the filled surfaces can be painted over with alkyd resin and acrylic paints as well as emulsion paints.

Storage:

Store containers tightly closed, child-proof and in a cool place, but not exposed to frost.

Notes

Do not use at object and ambient temperatures below +5 °C. Clean tools with water immediately after use. When using outdoors, apply a weather-resistant coat shortly after application.

Contains preservatives:

Chloromethylisothiazolinone/methylisothiazolinon e (3:1), benzoisothiazolinone, methylisothiazolinone. May cause allergic reactions. Advice for people allergic to isothiazolinone is available by calling 05541/7003-64.

Disposal:

Only recycle containers that are completely empty. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of uncured residues according to waste code EWC 08 04 10.

Item no./EAN/container size

009702000 4007954009703 1.3 kg



PUFAS Werk KG, Im Schedetal 1, 34346 Hann. Münden Tel. 05541 / 7003-01, www.pufas.de

Note

All information and data in this information sheet correspond to our practical experience and laboratory tests and are based on the current state of technology. However, they can only provide general information and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal liability can be derived from this information. It is the responsibility of the user to check the products for their suitability for the intended use under the respective conditions.

As of: 19 October 2020