

# PUFAS Bonding Fixative HF61

## PUFAS Haftfixierung

- special emulsion for textile and CV coverings with non-woven backing
- easily removable
- also suitable for floor heating systems
- immediately walkable
- solvent- and plasticizer-free

### Instructions for use:

PUFAS Bonding Fixative HF 61 for carpets is suitable for the fixation of carpets with fleece backing as well as for PVC and CV covering. Gluing can be done on all water-resistant surfaces in indoor areas like tiles, cement screed, PVC floors, floor-levelling mass, etc. It can also be used for heated floor structures.

There must be waterproof sealing should glue on parquet be desired.

### Technical specifications:

Components: synthetic resin dispersion, dispersion of modified resins, additives

Density: approx. 1 g/cm<sup>3</sup>

pH-value: approx. 7.2

Usage: 100-200 g/m<sup>2</sup>

### Substrate preparation:

The surface must be permanently dry, stable, humidity-resistant and free from parting compounds and contaminations (grease, dust, etc.). Level out cracks, holes, irregularities in thickness as well as rough screeds using AKAPLAN Floor levelling compound, AKAFLEX Wooden floor levelling compound or PUFAS Exterior Filler AKS. Pretreat strongly absorbent and sanding surfaces with PUFAS Deeply-Penetrating Primer LF - solvent free.

### Application:

Cut flooring to size. Turn over one half and then apply PUFAS Bonding Fixative HF 61 evenly onto the surface using a short-piled lambskin roller and allow it to evaporate completely until a transparent adhesive film has developed.

The drying time is between 30 and 60 minutes, depending on surface absorbing capacity, temperature and air humidity. The film must be transparent before the flooring can be laid in. The laid flooring must be thoroughly rubbed down afterwards. Do the same with the other half. Weight edges and joints down at the beginning if required.

### Removal:

The rest of the fixing emulsion can be easily removed using warm water under addition of PUFAS Wallpaper Remover TL after the floor covering has been removed. The contact time is approx. 15 minutes. Afterwards, remove the detached fixation using a plastic spatula and rinse the whole surface thoroughly with water.

The laying instructions of the floor covering manufacturers must be complied with.

### Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Remove adhesive residues with water.

Do not process below +10 °C sub-floor and room temperature.

Clean any working equipment with water after use.

### Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

### Storage:

Keep cool but protected from frost! Keep container well closed!

### Available sizes:

2,5 kg    4007955211020    021102001    REG