

Pufas Styrofoam Adhesive ST

PUFAS Styropor-Kleber ST

Ready to use emulsion-based adhesive for interior polystyrene panels.

Instructions for use

Pufas Styrofoam Adhesive ST is suitable for gluing polystyrene panels, under-wallpaper, visible, décor and insulating panels made from polystyrene, and decorative strips, etc.

Technical specifications:

Components: Styrene acrylate emulsion, fillers, thickening agents
pH-value: approx. 8-9
Density: approx. 1.70 g/cm³
Usage: approx. 750 g/m² (B2 indentations)

Surface preparation:

The surface must be absorbent, dry, firm and free of release agents (dust, grease, etc.) Remove loose masonry, old wallpaper and flaking paint. Make good cracks, holes and unevenness using *pufamur Super Bonding Filler* or *Fill&Finish Interior*. Pretreat highly absorbent, sanding and chalking surfaces using *PUFAS Deeply Penetrating Primer – Solvent Free*.

Application:

Evenly apply *Pufas Styrofoam Adhesive ST* to the surface using a spreading comb (B2 indentations). Place the panels to be glued on in the moist, adhesive bed and press. Where used for gluing onto ceilings we recommend you apply the adhesive to the back of the panels.

The pasted areas can be painted, wallpapered or stoppered after the adhesive has completely dried. To guarantee optimum adhesion of wallpapers and paints on polystyrene, a primer coat of thinned polystyrene adhesive (with 20 % water added) should be applied with a roller.

Immediately remove residual adhesive with water
Do not use if the surface and/or room temperature are below + 5° Celsius!
Clean tools in water after use.

Storage:

Store in a cool but frost-free place! Keep containers tightly sealed!

Available sizes:

400g	001106000	4007954011065
1 kg PE can	001101000	4007954011010
4 kg PE tub	001102000	4007954011027
8 kg PE tub	001103000	4007954011034
14 kg PE tub	001104000	4007954011041

