

# **PUFAS Gel Primer Control GT**

#### Area of application:

Ready-to-use special primer for wall and ceiling surfaces. Thanks to its gel structure, the primer can be easily and cleanly rolled, brushed or airless sprayed, even on ceilings. Ideal for priming slightly chalky substrates and machine-sanded surfaces. Not suitable for substrates made of wood, plastic, metal and glass.

## Properties:

- · Gel formula prevents splashing and dripping
- for neat application with roller, brush and airless spray equipment
- stabilizes surface and regulates suction
- Silane-modified for optimum adhesion even on smooth Substrates
- · Ready to use
- · for indoor and outdoor use

#### Technical data:

Raw material base: Pure acrylate, water, addi-

tives, dve

Colour: Slightly reddish colour Density: approx. 1.0 g/cm³

pH value: 7.5 – 8.5

GISCODE for coating

materials: BSW20

EU VOC limit value for (Cat.: A/h, Wb) = 30 g/l

this product: (2010)

VOC content of this

product: max. 0.5 g/l

#### Substrate:

For all mineral substrates (such as concrete, gypsum, lime and cement plaster, gypsum fillers, sand-lime brick, etc.) as well as for plasterboard, gypsum fibre, cement fibre and other drywall panels. The substrate must be dry, solid, clean and free of grease. Remove loose material, old wallpaper, glue-based paints and poorly adhering coatings. Pre-treat extremely absorbent or porous substrates with *Hydrosol Primer Deep-Penetrating LF*.

#### Application:

Apply undiluted with a short-pile roller, brush or suitable spray equipment. Can be recoated after approx. 8 hours (depending on the absorbency of the substrate, temperature and humidity – allow longer drying times in unfavourable conditions).

#### Notes

Please refer to the safety data sheet for safety-related information. Current safety data sheets are available on our website <a href="www.pufas.de">www.pufas.de</a> or atsds@pufas.de</a> .

#### **Storage**

Store in a cool place, well sealed and protected from frost. Keep out of reach of children.

### Disposal:

Only recycle containers that are completely empty. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of liquid residues in accordance with waste code no. EWC 08 01 12.

 Item no.EAN
 Container size

 019004000
 40079541900436
 10 I



As of: 18 June 2025

PUFAS Werk KG, Im Schedetal 1, 34346 Hann. Münden Tel. 05541 / 7003 -01, www.pufas.de