

# Pufas Stain and Moisture Blocker IF30

## Pufas Feuchtblocker Isolierfarbe IF30

Isolating paint to protect against damp and efflorescence on mineral surfaces, for indoor and outdoor use.

### Instructions for use:

*Pufas Stain and Moisture Blocker IF30* isolates water, nicotine and soot stains. Prevents salt efflorescence on all mineral surfaces, such as concrete, lime and cement-based plaster, clay tiles, etc.  
*Pufas Stain and Moisture Blocker IF30* is not suitable for gypsum surfaces and gypsum boards, which are not permanently dry.

### Technical specifications:

Components: Acrylic resin, pigments, cement, solvent  
Density: approx. 1.15 g/cm<sup>3</sup>  
Colour: white  
Gloss level: matt  
Flash point: approx. 57° Celsius  
Usage: 150-200 ml/m<sup>2</sup> per coat

### Surface preparation:

The surface can be moist, however, it must be firm and free of release agents. Remove efflorescence mechanically (brush) or using *decotric Saltpetre Remover*.

### Application:

Stir *dPufas Stain and Moisture Blocker IF30* well before use and apply using a brush or paint roller. Always apply two coats to achieve optimum isolation of the surface. Leave the first coat to dry for at least 8 hours before applying the second. Do not mix *Pufas Stain and Moisture Blocker IF30* with other paint systems however, can be thinned with max. 5 % white spirit to adjust its consistency. After the isolating paint has thoroughly dried, all cement-resistant paint systems can be used on it.  
Do not use at surface or in rooms below + 5° Celsius!

Clean tools immediately after use using *Pufas Paint Brush Cleaner R120* or *soluwash S*.

### Important information:

Please see the EU Safety Data Sheet for all safety-related data (EU-CLP).

### Storage:

Store in a cool place! Keep containers tightly sealed! Keep away from bare flames and ignition sources.

### Available sizes:

750 ml tin box	014401000	4007954144015
2 l tin tub	014402000	4007954144022

