

# PUFAS Algae and Mould STOP

## PUFAS Algen und Schimmel STOP

- chlorine-free and odourless
- removes mould, algae and green growth, also indoors, without unpleasant odour emissions
- for cleaning facades, roofs, paving stones, patios, fences etc.
- ideal for clay brick, stone, concrete etc.
- also suitable as substrate pre-treatment for coatings and facade impregnations
- self-acting and preventive

### Instructions for use:

Removes mould, algae and moss in interior areas – for example in sanitary installations. Cleans house walls, floors, roofs, garages, wood, tiles, clay tiles, stone, and concrete, etc. Can also be used as a cleaning surface pre-treatment for subsequent coats and facade impregnations.

### Technical specifications:

Components: didecyl dimethyl ammonium chloride  
 Density: approx. 1 g/cm<sup>3</sup>  
 pH-value: approx. 7-8

### Application:

Directly spray PUFAS Algae and Mould STOP onto the affected area from a distance of approx. 15-20 cm and leave to act. This occurs within 1-3 days. In case of severe contaminations, if no optical change appears in the treated surface, apply a further coat of PUFAS Algae and Mould STOP. Wash off any residues using clean water. After usage remove spray head and rinse with water.

### Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Clean any working equipment with water after use.

### Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

### Storage:

Store in a cool but frost-free place! Keep the containers tightly sealed!

### Available sizes:

500 ml	4007954070024	007002000	REG
500 ml	4007954070925	007012092	CIS

### Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.