

PUFAS Rapid Paint Stripper R60

PUFAS Abbeizer rasant R60

- removes paints and emulsion coats
- universal application
- also for cleaning stiff natural-bristle brushes
- CHC-free
- biodegradable

Instructions for use:

PUFAS Rapid Paint Stripper R60 is suitable for removing oil paints, synthetic-resin varnishes, dispersion paints as well as for cleaning stony-hard brushes (no plastic bristles). PUFAS Rapid Paint Stripper R60 works already after approx. 1 hour and does not run down on vertical surfaces. Wooden, metal and masonry bases are not attacked, plastics and bases not resistant to solvents can be attacked.

Free from dichloromethane and N-methyl pyrrolidone.

Technical specifications:

Components: butyl acetate, dimethyl sulphoxide and thickener

Density: approx. 0.92 g/cm³

Application:

Apply PUFAS Rapid Paint Stripper R60 using a brush and leave to soak. In the case of coatings that are difficult to strip, remove the partially dissolved layer using a spatula and repeat the process step. Afterwards, rinse the surface with water or PUFAS Paint Brush Cleaner R 120. Protect surfaces not to be pickled from splatters by covering them with a film. Paint remnants must be disposed of via a hazardous waste collection point in accordance with the regulations.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Clean any working equipment with water after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Keep cool! Store container well closed and keep it away from ignition sources!

Available sizes:

375 ml	4007954069011	006901000	REG
750 ml	4007954069028	006902000	REG
2.5 l	4007954069035	006903000	REG



Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.