

PUFAS Cement Film Cleaner ZE

PUFAS Zementschleier Entferner ZE

- high-performance concentrate
- removes mortar residue, cemen-titious deposits and lime scale
- for tiles, engineering bricks, facing masonry units, fully vitrified stoneware, patio flags and similar acid-resistant surfaces

Instructions for use:

PUFAS Cement Film Cleaner ZE quickly and effortlessly removes lime and cement residues from acid-resistant tiles, clinker, terrace slabs, etc.

Also ideally suited for removing limescale deposits in sanitary areas (e.g. on fittings and washbasins).

Before use, check the resistance of the surface on a small test area, as it corrodes surfaces, which are not acid-resistant such as marble, cast stone, and similar.

Technical specifications:

Components: phosphoric acid and tensides (surfactants)

Density: approx. 1.1 g/cm³

pH-value: approx. 0.7-1

Usage: 100 ml/m²

Substrate preparation:

Before use the product should be always tested on a small test area to check for compatibility, as non-acid-resistant surfaces such as it corrodes marble, cast stone, etc.

Application:

For lightly soiled surfaces thin PUFAS Cement Film Cleaner ZE with water in a ratio of 1:10, for highly soiled surfaces with a ratio of 1:5 to max. 1:3, then apply to the areas to be cleaned and spread using a sponge. Leave to take effect for several minutes and then wash off thoroughly using water. For use in sanitary areas, thin PUFAS Cement Film Cleaner ZE in a ratio of 1:5 to 1:10 with water.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Clean any working equipment with water after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool place. Keep container tightly sealed.

Available sizes:

1 l	4007954048016	004801000	REG
1 l	4007954048917	004801092	CIS

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.