

PUFAS Silicon Resin Façade Paint

- extra-white, scrub-resistant facade coating
- with long-term film protection against algae and green growth
- highly water-repellent
- very high water vapour permeability
- excellent hiding power
- very low susceptibility to soiling

Technical data:

Components:	Synthetic resin dispersion, silicone resin, titanium dioxide, extenders, water, cellulose ether and additives
Density:	approx. 1.6 g/cm ³
pH value:	8.5-9
Consumption:	150-200 ml/m ² per coating

Surface preparation:

The surface must be dry, stable and free from parting compounds (dust, oil, mould, algae, etc.). Clean surfaces overgrown with mould, moss or algae mechanically at first or pre-treat them with *PUFAS Algae and Mould STOP*. Prime strongly absorbent, sanding and chalking surfaces with *PUFAS Silicone Resin Primer*. Level cracks, holes and irregularities using *decotric External and Adhesive Filler* or *PUFAS Exterior Façade Filler*. Be sure to cover glass surfaces since paint splatter on glass is very difficult to remove.

Application:

Apply *PUFAS Silicone Resin-Façade Paint* using roller, brush, scrubber or the airless spraying method. Depending on absorbency of the surface, the paint can be diluted with max. 10 % water for the first painting. The second application of paint should be applied undiluted after the first paint application has dried. *PUFAS Silicone Resin Façade Paint* can be tinted with max. 3 % *pufamix Universal Concentrated Colorants (only LW oxide types)*.

Clean any working equipment with water immediately after use.
Do not process below +5° Celsius sub-floor and room temperature!

Important information:

Please see the EU Safety Data Sheet for all safety-related data (EU-CLP).

Storage:

Keep cool but protect from frost! Keep container well closed!

Container sizes:

5 l PE oval bucket	014003000 / EAN 4007954140031
10 l PE oval bucket	014004000 / EAN 4007954140048
12,5 l PE oval bucket	014005000 / EAN 4007954140055

