

Technical Data Sheet

PUFAS Woodchip Paint R25 PUFAS Flüssige Rauhfaser R25

Use

Textured emulsion paint for indoor wall and ceiling surfaces.

- decorative woodchip texture, for roller and spray application
- efficient application
- seamless texture
- opaque white finish
- water vapour-permeable
- solvent-free and low-emission

Technical Data:

Constituents: Polymer dispersion, titanium dioxide, wood fibre, mineral fillers, water, additives

colour: white

Density: ca. 1,58 g/cm³

pH-value: ca. 8

Gloss level: matt

Substrate:

For all mineral substrates (e.g. concrete, masonry, filling compounds, gypsum plaster, cement render and lime render), gypsum plasterboard and other drylining board, firmly adhering emulsion paint coats and overcoatable wallpaper and wall coverings. Substrate shall be dry, clean, strong, uniformly absorbent, and free from dust and grease. Remove loose material, existing wallpaper and badly adhering coatings from substrate. Prime highly absorbent, friable and chalking substrates with **baufan®** Deeply Penetrating Primer – solvent-free. Repair cracks, holes and irregularities with suitable **baufan®** filler.

Application:

Stir well prior to use and apply with roller (recommended pile thickness 16-18 mm), brush or suitable spray equipment (not airless). As primer, paint may be diluted with max. 10 % water, as finishing coat with max. 5 %, applied after first coat has fully dried. Application of paint in two thin coats, working crosswise, is recommended to achieve uniform texture, also with roller or brush. When coating larger areas, always work with live edges to prevent laps (flashing). Wash tools with water immediately after use.

Consumption:

ca. 500 – 800 ml/m² per coat. Determine exact consumption by applying a sample to the object.

Tinting:

With Universal Concentrated Colorants or with max. 5 % Full-Tone and Tinting Paint. Greater quantities will increasingly change woodchip effect.

Note:

Mask areas not to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Do not inhale spray mist. Refrain from eating, drinking and smoking while using paint. Wear goggles. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling. Approx. 5 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions. +5 °C to + 30 °C for material, ambient air and substrate

For safety-related information, please refer to the safety data sheet. Current safety data sheets are available on our website www.pufas.de or at sds@pufas.de.

EU VOC limit value for this product: (Cat.: A/a, Wb) = 30 g/ltr (2010) Max. VOC content of this product: 1 g/ltr
GISCODE für Beschichtungsstoffe: BSW20.

Contains biocidal products (preservatives):

Contains biocidal products (preservatives):
Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone, octylisothiazolinone. May cause an allergic reaction.

Storage:

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: see batch label.

Container / Art.No.: / EAN:

2,5 l	010811000	4007954 108017
5 l	010812000	4007954 108024
10 l	010813000	4007954 108031
15 l	010814000	4007954 108048



Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.