

KVS Cellulose Wallpaper Adhesive KVS Zell-Leim

Wallpaper adhesive of reliable, tested quality.

Instructions for use: KVS Cellulose Wallpaper Adhesive is suited for woodchip wallpapers, light and

heavy weight paper wallpapers, embossed wallpapers, textile wallpapers, vinyl

wallpapers and similar wall coverings.

Technical specifications: Components: Carboxmethylcellulose

Density: 0.6 g/cm³ pH-value: 7-8

Solubility: ready to use in approx. 30 minutes

Usage: Approx 200 ml/m²

Surface preparation: The surface must be dry, firm and free of dust and grease. Remove old, peeling

wallpapers and distemper paints using *PUFAS Wallpaper Remover*. Make good cracks and holes using *PUFAS Interior* or *PUFAMUR Super Bonding Filler*.

Pre-treat strongly absorbent, abrasive and chalky surfaces with *PUFAS Deeply-Penetrating Primer – solvent free*. Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using

PUFAS Insulating Spray White.

To make a subsequent change of wallpaper easier, we recommend priming the surface first with *PUFAS Wallpaper Base Primer 'Tapeten-Wechselgrund'*, es-

pecially where washable wallpapers are used.

Application: Stirring vigorously, sprinkle 200 g KVS Cellulose Wallpaper Adhesive into 5 I

clean, cold water and continue to stir for a few minutes. Leave for approx. 30

minutes and then stir vigorously again.

Evenly apply KVS Cellulose Wallpaper Adhesive to the wallpaper using a wallpapering machine or brush. Fold the pasted ends inwards and hang after an adequate soaking time. Always observe the wallpapering machine and wallpa-

per manufacturer's instructions for use.

We recommend to add approx. 20 % *PUFAS Wallpaper and Border Adhesive* for use on hardly absorbent surfaces and to increase the moisture resistance.

Do not use if the object and/or room temperature are below + 5° Celsius!

Remove adhesive residues using a damp cloth.

Clean tools in water after use.

Storage: Store in a cool and dry place! Keep the bag tightly sealed

Available sizes: 200 g paper bag 002402000

7.5 kg paper bag 002403000 25 kg paper bag 002401000