

## extra Wallpaper Adhesive - Super Economy Pack extra Tapeten-Kleister - Super-Sparpack

### Instructions for use:

The adhesive is suitable for pasting light to heavy weight paper wallpapers on plaster, concrete, gypsum and plasterboards. Particularly suited for rough surfaces.

### Technical specifications:

Components: Starch ether, rheological additive  
Density: approx. 0.4 g/cm<sup>3</sup>  
pH-value: approx. 8  
Solubility: Ready for use after approx. 30 minutes  
Usage: approx. 200 ml/m<sup>2</sup>

### Surface preparation:

The surface must be dry, firm and free of dust and grease. Remove old, peeling wallpapers and distemper paints using *decotric Wallpaper Remover*. Make good cracks and holes using *decofill Interior* or *decomur Super Bonding Filler*.

Pre-treat strongly absorbent, abrasive and chalky surfaces with *decotric Deeply Penetrating Primer – Solvent Free*. Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using *decotric Insulating Spray*.

### Application:

Stirring vigorously, sprinkle *extra Wallpaper Adhesive* into clean, cold water (see table) and continue to stir for a few minutes. Leave for approx. 30 minutes and then stir vigorously again.

Evenly apply the adhesive to the wallpaper using a brush. Fold the pasted ends inwards and hang after an adequate soaking time. Always observe the wallpaper manufacturer's instructions for use.

We recommend to add 750 g *decotric Wallpaper and Border Adhesive* per 3-4 litres mixed *extra Wallpaper Adhesive* for use on hardly absorbent surfaces and to increase the moisture resistance.

Do not use if the surface and room temperature are below + 5° Celsius!  
Remove adhesive residues using a damp cloth.  
Clean tools in water after use.

### Mixing ratio for 500 g packet:

for	Mixing ratio	Quantity of water per 500-g packet	Coverage of a 500-g packet
Pre-pasting	1:25	12,5 l	Approx. 70 m <sup>2</sup>
Light weight wallpapers	1:20	10 l	50-60 m <sup>2</sup>
Woodchip wallpaper	1:15	7.5 l	35-40 m <sup>2</sup>
Heavy wallpapers	1:10-1:12	5-6 l	25-30 m <sup>2</sup>

### Mixing ratio for 1 kg packet:

for	Mixing ratio	Quantity of water per 1 kg packet	Coverage of a 1 kg packet
Pre-pasting	1:25	25 l	Approx. 140 m <sup>2</sup>
Light weight wallpapers	1:20	20 l	100-120 m <sup>2</sup>
Woodchip wallpaper	1:15	15 l	70-80 m <sup>2</sup>
Heavy wallpapers	1:10-1:12	10-12 l	50-60 m <sup>2</sup>

### Storage:

Store in a cool and dry place!

### Available sizes:

500 g collapsible box 002701000  
1 kg collapsible box 002702000