

Professional Glazier's Putty

Profi Glaserkitt

High quality window filler for single and repair glazing to DIN 18545 A.

Instructions for use:

Professional Glazier's Putty is made from natural raw materials and is ideally suited for single and repair glazing for windows with wood, steel and concrete frames.

Technical specifications:

Components:	Linseed oil, natural chalk
Density:	approx. 2.0 g/cm ³
Colour:	beige
Setting time:	4-6 weeks

Surface preparation:

The window frame must be clean, dry and free of grease. The rabbets must be primed. However, to guarantee optimum bonding of the linseed oil filler, the primer should not be applied so thick that it closes off the pores in the wood.

Application:

After kneading *Professional Glazier's Putty*, press firmly into the rabbet and smooth the surface using a glazing knife. It is very important that any condensation, which occurs during the drying time, is prevented from penetrating the filler bed. As the filler needs oxygen to bond, double windows should not be assembled immediately after glazing.

After the filler has cured, after 4-6 weeks at the latest, it must be painted over with weatherproof, elastic paint. If using acrylic paints you should always carry out preliminary tests first.

Clean tools in *decotric Paint Brush Cleaner* or *aka Soluwash S* immediately after use.

Storage:

Store in a cool, dry but frost-free place! Keep the containers tightly sealed!

Article No.:

059803000

Available sizes:

750 g can