

# PUFAS Decorative Effect Plaster - coarse

## PUFAS Dekor Effekt Putz grob

- ready-to-use
- easy application with roller or brush
- highly water vapour permeable
- preservative-, solvent- and plasticizer-free
- tintable with Universal Concentrated Colorants (LW oxide types)
- suitable as decorative finishing coat
- overcoatable
- two plaster textures coarse – 1 mm aggregate size

### Instructions for use:

For all mineral substrates, gypsum plasterboard, drylining board and emulsion paint coats. Substrate shall be dry, clean, solid, strong and free from adhesion- impairing substances. Pretreat highly absorbent, friable and chalking substrates with high-quality primer. Repair cracks, holes and irregularities with suitable filler.

### Technical specifications:

Components: Minerals parts, potassium silicate, dispersion, Titandioxid, water and additives  
 Density: approx. 1.71 g/cm<sup>3</sup>  
 pH-value: approx. 10.5  
 GISCODE for Coating material BSW10

### Surface preparation:

Substrate shall be dry, strong and free from adhesion-impairing substances (e.g. dust, mould oil). Pretreat highly absorbent, friable and chalking substrates and cut edges of gypsum plasterboard with primer. Make good cracks and holes as well as unevenness substrates using a filler.

### Application:

Stir well before use. and apply with brush or roller. Depending on the temperature and humidity allow to dry after application for approx. 8-12 hours

### Tinting:

For colored coatings, Decorative Effect Plaster – coarse can be tinted with max. 5 % PufaMix concentrated colorant.

### Overpainting:

Decorative Effect Plaster – coarse is particularly well suited as decorative final coat or if desired it can also be painted over with emulsion paint.

### Consumption:

1 kg for approx 2 sqm by single coating, depending on the absorption and structure of the substrate.

### Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use at building fabric and room temperatures below +5 °C.

Wash tools with water immediately after use. In case of contact with eyes, rinse immediately with water.

For spray application, do not inhale spray mist.

Do not allow to enter drains, sewers, surface waters or ground.

### Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

### Storage:

Store in cool, dry place, out of reach of children. Keep opened containers tightly closed. Hand over only fully emptied containers for recycling.

### Available sizes:

8 kg	4007955606024	060602301	REG
15 kg	4007955606031	060603301	REG