

PUFAS EURO 3000 Vlies Direkt - Blue control

Instructions for use:

PUFAS EURO 3000 Vlies Direkt is ideally suitable for pasting non-woven wallpapers onto the wall.

Technical specifications:

Components: Starch ether, poly vinyl acetate powder

Density: approx. $0.3 - 0.4 \text{ g/cm}^3$

pH-value: approx. 8 – 9

Solubility: Ready for use after approx. 5 minutes

Usage: approx. 200 ml/m²

Application:

Stirring vigorously, sprinkle PUFAS EURO 3000 Vlies Direkt into 6 l. clean, cold water and continue to stir for some minutes. Leave for approx. 5 minutes and then stir vigorously again. The prepared adhesive is blue coloured.

Application onto the surface:

For the modern wallpapering technique – e.g. for pasting form-stable non woven wallpaper and many others – wallpaper manufacturers recommend pasting the surface. Apply the stirred PUFAS EURO 3000 Vlies Direkt for 1 to 2 strips of wallpaper evenly to the surface with a lambswool roll. Lay strip of wallpaper on the fresh bed of paste and press on evenly.

Application onto the wallpaper:

Paste wallpaper evenly with PUFAS EURO 3000 Vlies Direkt and fold over. After sufficient softening, apply on impact and press on.

After dryness the adhesive is transparent.

Always observe the wallpaper manufacturer's instructions for use.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Remove adhesive residues using a damp cloth.

Do not use if the object and room temperature are below + 5° Celsius!

Clean tools in water after use

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool and dry place

Mixing ratio:

wixing ratio.		
for	non woven wallpaper, heavy wallpaper	
Mixing ratio	1:20	
Quantity of water per 300 g packet	61	
Coverage of a 300 g packet	25 – 30 m ²	

Available sizes:

200 g	4007954217115	021701031	OE
300 g	4007954217122	021702031	OE