

PUFAS EURO 3000 Non-Woven Adhesive OE

Instructions for use:

PUFAS EURO 3000 Vlies is ideally suitable for hanging nearly all kind of non-woven wallpapers by pasting the wall technique as also traditional technique of application. Usable indoor for mineral surfaces and gypsum boards

Technical specifications:

Components: Starch ether, polyvinyl acetate powder
 Density: approx. 0.3 – 0.4 g/cm³
 pH-value: approx. 10 - 11
 Solubility: Ready for use after approx. 5 minutes
 Usage: approx. 200 ml/m²

Surface preparation:

The surface must be dry, firm, and dust and grease-free. Remove old, peeling wallpapers and distempers using PUFAS Wallpaper Remover TL. Make good cracks and holes using PUFAS Interior filler FSI or PUFAMUR Filler. Pretreat highly absorbent, sanding and chalking surfaces using PUFAS Deeply- Penetrating Primer LF – solvent free.

Application:

Stirring vigorously, sprinkle PUFAS EURO 3000 Vlies into 4 l clean, cold water and continue to stir for some minutes. Leave for approx. 5 minutes and then stir vigorously again. Application onto the surface: for pasting form-stable non-woven wallpaper and many others – wallpaper manufacturers recommend pasting the surface. Apply the stirred PUFAS EURO 3000 Vlies for 1 to 2 strips of wallpaper evenly to the surface with a lambswool roll. Lay strip of wallpaper on the fresh bed of paste and press on evenly. Application onto the wallpaper: Paste wallpaper evenly with PUFAS EURO 3000 Vlies and follow instructions of wallpaper manufacturer. Always observe the wallpaper manufacturer's instructions for use.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Remove adhesive residues using a damp cloth.

Do not use if the object and room temperature are below + 5° Celsius!

Clean tools in water after use

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool and dry place

Mixing ratio:

for	non woven wallpaper, heavy wallpaper
Mixing ratio	1:20
Quantity of water per 200 g packet	4 l
Coverage of a 200 g packet	25 – 30 m ²

Available sizes:

200 g 4007954219119 021901031 OE