

## EURO 3000 Special Adhesive EURO 3000 Spezialkleister

**Instructions for use:** *EURO 3000 Special Adhesive* is ideally suitable for pasting light and heavy woodchip wallpapers, paper wallpapers and vinyl wallpapers on mineral surfaces and gypsum boards.

**Technical specifications:**

Components:	starch ether, poly vinyl acetate powder
Density:	approx. 0.3-0.4g/cm <sup>3</sup>
pH-value:	approx. 8-9
Solubility:	ready for use after approx. 5 minutes
Usage:	approx. 200 ml/m <sup>2</sup>

**Surface preparation:** The surface must be dry, firm, and dust and grease-free. Remove old, peeling wallpapers and distempers using *PUFAS Wallpaper Remover*. Make good cracks and holes using *PUFAMUR Super Bonding* or *PUFAS Interior Filler*. Pretreat highly absorbent, sanding and chalking surfaces using *PUFAS Deeply-Penetrating Primer – solvent free*. Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using *PUFAS Insulating Spray White*. We recommend applying a sub-coat of *PUFAS Wallpaper Primer - White* before hanging highly translucent wallpapers and where surfaces are highly contrasting. To make a subsequent change of wallpaper easier, especially where washable wallpapers are used, we recommend priming the surface first with *PUFAS Wallpaper Base Primer 'Tapeten-Wechselgrund'*.

**Application:** Stirring vigorously, sprinkle *EURO 3000 Special Adhesive* into clean, cold water (see table) and continue to stir for some minutes. Leave for approx. 5 minutes and then stir vigorously again.

Evenly apply *EURO 3000 Special Adhesive* to the wallpaper. Fold the pasted ends inwards and hang after an adequate soaking time.

We recommend to add 750 g *PUFAS Wallpaper and Border Adhesive* per packet *EURO 3000 Special Adhesive* for use on hardly absorbent surfaces and to increase the moisture resistance.

Always observe the wallpapering machine and wallpaper manufacturer's instructions for use.

Remove adhesive residues using a damp cloth.

Do not use if the surface and room temperature are below + 5° Celsius!

Clean tools in water after use.

**Mixing ratio:**

for	Mixing ratio	Quantity of water per 200-g packet	Coverage of a 200-g packet
Pre-pasting	1 : 50	15 l	100-130 m <sup>2</sup>
light wallpapers	1 : 34	10 l	55-60 m <sup>2</sup>
Woodchip wallpaper	1 : 30	9 l	45-55 m <sup>2</sup>
Heavy wallpaper, Vinyl wallpaper	1 : 22	6,6 l	33-44 m <sup>2</sup>

**Storage:** Store in a cool and dry place!

**Available sizes:**

200 g box	022101000
300 g box	022112000