

Pufas Joint-Fix

Pufas Fugen-Fix

Instructions for use:

Joint-Fix is perfectly suitable for repair work on joints of ceramic and glass tiles, tiles and mosaics. *Joint-Fix* is not suitable for floors.

Technical specifications:

Components: Styrene-acrylate dispersion, filling material and additives
Colours: white
Density: approx. 1.80 g/cm³
pH value: approx. 8-9
Drying period: 4-7 hours depending on coating thickness, surface absorbing capacity and ambient temperature

Substrate preparation:

The joints to be repaired must be dry, stable and free from parting compounds (dust, grease, soap residues, etc.). Remove loose material from the joints by scraping them out..

Application:

Knead tube well before each use. Press *Joint-Fix* directly into the damaged places and carefully remove any protruding filler using a rubber spatula, for instance. The repaired joint must be filled in without any gaps. The tiles need to be cleaned using a damp cloth or sponge before the filler has fully dried through. Porous, matte and unglazed tiles must be covered before grouting (e.g. with adhesive tape).

The mends will be waterproof once decotric Joint Repair white has fully dried. Do not process below +5° Celsius sub-floor and room temperature! Clean tools with water immediately after use.

Note:

Do not use if the surface and/or room temperature are below + 5° Celsius!

Clean tools in water after use.

Storage:

Keep container well closed and cool but frost-protected. Temperature resistance during transport up to max. -15 °C.

Available sizes:

400g 4007954042120 004201031

