

Wallpaper Adhesive Normal

Tapetenkleister Normal

Area of application:

Wallpaper paste for sticking normal, lightweight paper wallpaper.

Properties

- For normal, lightweight paper wallpaper
- Ready to use in approx. 30 minutes

Technical data:

Raw material base: Starch ether, cellulose ether and additives

approx. 0.41 g/cm³

Bulk density:

approx. 10.5

pH value:

Substrate preparation:

Only wallpaper on dry, clean, smooth and solid surfaces. Remove glue paint, wallpaper residue and loose paint. Repair cracks, holes and uneven areas with filler. Pre-coat sandy and chalky surfaces with LF deep primer. Pre-paste highly absorbent surfaces (see table) or prime them. Pre-treat coarse-grained plaster with waste paper.

Wallpapering:

Apply the paste evenly and generously to the wallpaper strips, fold them together and, after allowing the recommended soaking time, stick them to the wall with the edges aligned. The wallpaper manufacturer's instructions for use must be followed.

Heavy wallpaper, e.g. woodchip, textile, grass, wood and plastic-coated wallpaper, should be glued with special adhesive.

use	Seed	Water In litres	pack Sufficient for
Pre-pasting	1:65	8	50–60 m
normal wallpaper	1:50	5–6	30 – 35 m 6 – 7 rolls

Notes:

Do not process below +5 °C. Remove paste residues immediately with a damp cloth. Clean tools with water after use. Free from isothiazolinones, therefore the mixed paste should be used quickly.

Please refer to the safety data sheet for safety-related information. You can obtain the latest safety data sheets via or our website

www.Dufas.de/www_decotric.de
sdstOpufas.de/sdstOdecotric.de

or at

Storage:

Keep containers tightly closed, dry and cool, but frost-free. Store in a dry place. Keep out of reach of children.

Disposal:

Only recycle containers that are completely empty. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of liquid residues according to waste code no. EWC 08 04 10.

Item no.

002801080

EAN

4002175028014

Package size

125 g



Note

All information and data in this information sheet correspond to our practical experience and laboratory tests and are based on the current state of technology. However, they can only provide general information and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal liability can be derived from this information. It is the responsibility of the user to check the products for their suitability for the intended use under the respective conditions.