# Wallpaper Adhesive Special

# Spezialkleister

# Area of application:

Special paste made from high-quality cellulose with synthetic resin for bonding woodchip, textured, embossed, non-woven and paper wallpapers.

# **Properties**

- for woodchip, textured and embossed wallpapers
- · with methyl cellulose
- · synthetic resin-reinforced
- · reliable bond strength
- · high initial adhesion
- · easy to correct
- · free from preservatives

#### Technical data:

Raw material base: Starch ether, polyvinyl acetate powder

pH-value: approx.9

Bulk density: approx. 0.50 g/cm<sup>3</sup>

### Substrate preparation:

The substrate must be dry, sound, level, dust-free and free of grease. Remove old wallpaper and poorly adhering paint. Fill holes and uneven areas. Treat sanding and chalky substrates with deep primer. Pre-paste highly absorbent substrates (mixing ratio 1:40) or also prime.

# Application:

Sprinkle the contents of the package into clean, cold water (see table) while stirring vigorously and continue stirring for a short time. Stir vigorously again after 20 minutes. Coat the wallpaper strips evenly and fold them together. After allowing the specified soaking time to elapse, stick the wallpaper strips together and press down to remove any bubbles.

The processing instructions of the wallpaper manufacturer must be observed.

Intended use	Preparatio n:	Water quantity:	Conte nts suffici ent for:
Pre-paste	1:40	8	50-70 m <sup>2</sup>
Woodchip, textured, vinyl and heavy wallpaper	1 : 20	4	20-25 m²

### **Notes**

For poorly absorbent substrates and to increase moisture resistance, we recommend adding 750 g of wallpaper paste per paste pack.

Remove any paste residue from the front of the wallpaper immediately with a damp cloth. Do not use at temperatures below +5 °C. Clean tools with water after

# Storage:

Store in a cool, dry place out of reach of children.

### Disposal

Only recycle containers that are completely empty. Dried material residues can be disposed of with household waste or as construction waste. Dispose of liquid residues in accordance with waste code no. EWC 08 04 10. Do not allow to enter drains, waterways or the ground.

EAN no.: 4007954029114 200 g pack

Art. No.: 002901031



decotric GmbH, Im Schedetal 1, 34346 Hann. Münden Tel. 05541 / 7003-02, www.decotric.de

As of: 09/09/2021

### Note: