

## decoself Wallpaper Adhesive Special decoself Spezial Kleister

### Instructions for use:

*decoself Wallpaper Adhesive Special* - Special is suitable for pasting woodchip wallpapers, paper wallpapers, vinyl wallpapers and similar wall coverings.

### Technical specifications:

Components: Starch ether, polyvinyl acetate powder  
Apparent weight: approx. 0.50 g/cm<sup>3</sup>  
pH-value: approx. 8  
Solubility: ready for use after approx. 30 minutes  
Usage: approx. 200 ml/m<sup>2</sup>

### Surface preparation:

The surface must be dry, firm, dust and free of release agents (dust, grease, etc.) Remove all old, loose wallpapers and distempers using *PUFAS Wallpaper Remover*. Make good cracks and holes using *Fill&Finish interior* or *pufamur Super Bonding Filler*.

Pre-treat strongly absorbent, abrasive and chalky surfaces with *PUFAS Deeply Penetrating Primer – Solvent Free*. Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using *PUFAS Stain Blocker Spray S10*.

To make a subsequent change of wallpaper easier, we recommend priming the surface with *PUFAS Wallpaper Primer – Easy strip-off WG*, especially when hanging washable wallpapers.

### Application:

Stirring vigorously, sprinkle *decoself Wallpaper Adhesive Special* - Special into clean, cold water and continue to stir for a few minutes. Leave for approx. 30 minutes and then stir vigorously again.

Evenly apply the adhesive to the wallpaper using a wallpapering machine or brush, fold the fold the pasted ends inwards and hang after an adequate soaking time. Always observe the wallpapering machine and wallpaper manufacturer's instructions for use.

We recommend to add 750 g *PUFAS Wallpaper Adhesive BW plus* per 200 g packet *decoself Wallpaper Adhesive Special* for use on hardly absorbent surfaces and to increase the moisture resistance.

Do not use if the surface and room temperature are below + 5° Celsius!  
Remove adhesive residues using a damp cloth.  
Clean tools in water after use.

### Mixing ratio:

for	Mixing ratio	Quantity of water per 200-g packet	Coverage of a 200-g packet
Pre-pasting	1:40	8	60-80 m <sup>2</sup>
Heavy wallpapers	1:20	4	22-26 m <sup>2</sup>
Woodchip wallpapers	1:20	4	22-26 m <sup>2</sup>
Special adhesive tasks, unprinted embossed wallpapers	1:15	3	10-15 m <sup>2</sup>

### Storage:

Store in a cool and dry place!

### Available size:

200 g collapsible box

002901000

4002175029110

#### Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.