

decoself Normal D/PL/CZ/BG

decoself Normal D/PL/CZ/BG

Economy priced wallpaper adhesive, quality-tested.

Instructions for use: decoself Normal is suitable for pasting lightweight wallpapers.

Technical specifications: Carboxy methyl cellulose, starch ether Components:

> approx. 0.40 g/cm3 Density:

pH-value: approx. 8

Solubility: Ready for use in 30 minutes

Usage: approx. 200 ml/m²

Surface preparation: The surface must be dry, firm, dust and free of release agents (dust, grease,

> etc.) Remove all old, loose wallpapers and distempers using PUFAS Wallpaper Remover. Make good cracks and holes using Fill&Finish Interior or pufamur

Super Bonding Filler.

Pre-treat strongly absorbent, abrasive and chalky surfaces with *PUFAS Deeply* Penetrating Primer - Solvent Free. Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using PUFAS Stain Blocker Spray S10. We recommend a first coat with PUFAS Wallpaper Adhesive BW plus if hanging highly translucent wallpapers and

where surfaces are highly contrasting.

Instructions for use: Stirring vigorously, sprinkle decoself Normal into clean, cold water (see table)

and continue to stir for a few minutes. Leave for approx 30 minutes and then stir

vigorously again.

Evenly apply decoself Normal to the wallpaper using a brush or wallpapering machine, fold the pasted ends inwards and hang after an adequate soaking

time. Hang the wallpaper according to the manufacturer's instructions.

Clean tools with water immediately after use.

Do not use if the object and/or room temperature are below + 5° Celsius!

Remove adhesive residues using a damp cloth

Mixing ratio:

for	Mixing ratio	Quantity of water per 125 g packet	Coverage of a 125 g packet
Pre-pasting	1:65	81	50-60 m ²
Lightweight wallpapers	1:48	61	35 m²
Heavy wallpapers	1:40	51	30 m²

Storage: Store in a cool and dry place!

Available size: 125 g collapsible box 002801080