

PUFAS Cera-Color Special 3 in 1 OE

Area of application:

Silk matt water-based varnish for coating ceramic wall tiles in interior areas

Properties:

- 3 in 1 primer, finishing coat and sealing in one step
- · direct application on tiles without sanding or additional primer
- ideal for bathroom, kitchen and lavatory
- very good covering properties
- tintable with pufamix universal concentrated colorants

Technical data

Raw material base: Special plastic dispersion, mineral components titanium dioxide, water, additive

Density: approx. 1.26 g/cm³

pH value: 4-5

Substrate preparation:

The tiles must be dry, clean, dust-free and free of grease. Remove any soap residue, lime and silicone residues. e.g. with decotric silicone remover. Clean the tiles thoroughly – e.g. with decotric tile and joint cleaner. Remove loose parts. Repair damaged joints or dowel holes with joint repair and allow to dry thoroughly before further processing. Mask off adjacent areas such as floors and sanitary fixtures.

Processing:

Apply the tile varnish two to three times with a short-pile paint roller, allowing to dry between coats. Remove the adhesive tape immediately after applying the paint. The paint is touch-dry after approx. 60 minutes and can be painted over after approx. 4–6 hours – in unfavourable conditions (e.g. low temperature or high humidity), the drying time may be longer. The paint is completely dry after five days.

For coloured coatings, the tile varnish can be tinted with up to 10 ml of *pufamix universal tinting concentrate* per 750 ml can.

Consumption:

Approx. 100 ml/m². The contents are sufficient for approx. 7.5 m² with one coat and approx. 3.75 m² with two coats.

Notes:

+The painted surface can be cleaned with standard mild household cleaners (do not use abrasive cleaners). Not suitable for wet areas. Do not use at temperatures below 8°C. Clean tools with water immediately after use. Caution! Spraying may produce dangerous respirable droplets. Do not inhale aerosols or mist.

Please refer to the safety data sheet for safety-related information. Current safety data sheets are available on our website www.pufas.com or atsds@pufas.de .

Storage:

Store containers tightly closed and in a cool place, but not exposed to frost. Keep out of reach of children.

Disposal

Only recycle containers that are completely empty. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of uncured residues in accordance with EWC waste code no. 08 01 11.

 Item no.
 EAN
 Container size

 027402031
 4007954274125
 750 ml



PUFAS Werk KG, Im Schedetal 1, 34346 Hann. Münden Tel. 05541 / 7003 -01, www.pufas.com

As of: 29 October 2024

Note: