

PUFAS Wall-Protect Finish 3 in 1 OE

Area of application:

Water-based PU protective varnish for many interior and exterior surfaces. Suitable for vertical surfaces such as concrete, wallpaper, emulsion paints, tiles and wood. Ideal as a finish for *Pufas Cera-Color Special 3 in 1 OE* for a splash-proof and cleaner-resistant surface. Not suitable for surfaces where water can remain for a long time.

Properties:

- transparent
- satin-matt
- Impact, shock and scratch resistant
- inside and outside
- UV-resistant
- does not yellow

Technical data:

Raw material basis: One-component special plastic lacquer, solvent, water, additives

Density: approx. 1.04 g/cm³
pH value: 7 - 8

Substrate pre-treatment:

The substrate must be clean, free of dust and grease, absolutely dry and pH-neutral.

Processing:

Depending on the desired protection, apply the varnish once or twice with a roller or brush. The surface is touch-proof after 30 minutes and can be recoated after approx. 2 - 4 hours - the drying time may be longer depending on the temperature and humidity. After four days, the painted surface is fully resilient. Surface cleaners should be tested in advance for suitability in an inconspicuous area.

Consumption:

Approx. 100 ml/m². The content is sufficient for approx. 7.5 m² with a single coat.

Notes:

Apply a test coat before use. If several containers are used, make sure they are from the same batch. Do not apply below +5 °C. Clean tools with water immediately after use.

For safety-relevant data, please refer to the safety data sheet. Current safety data sheets are available on our website www.pufas.com or at sds@pufas.de

Storage:

Keep container tightly closed and store in a cool but frost-free place. Keep out of the reach of children.

Disposal:

Only dispose of empty containers for recycling. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of product residues according to EWC waste code no. 08 01 12.

Article no.
113602031

EAN
4007954136126

Container size
750 ml



Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.