

PUFAS Reno-inn quick renovation paint S130

Pufas Reno-inn Schnell-Renovierfarbe S130

Low-odour, insulating paint with excellent hiding power for highly soiled indoor surfaces. Contains solvents.

Instructions for use:

PUFAS Reno-inn quick renovation paint S130 reliably isolates nicotine, water, soot and grease stains on all mineral surfaces (plaster, concrete, clay tiles, etc.), wallpapers, emulsion paints, gypsum boards, polystyrene sections and ceiling panels, glass cloth as well as wood. *PUFAS Reno-inn quick renovation paint S130* can be used in all areas of the home and due to its outstanding hiding power and isolating effect is particularly suitable for soiled areas in guesthouses, schools, stairwells, work-shops, etc. Not suitable for painting plastic and metal.

Technical specifications:

Components:	low-odour, aromatic compounds-free isoparaffins, pure acrylate resin, titanium dioxide
Density:	approx. 1.49 g/cm ³
Flash point:	> 61° Celsius
Gloss level:	matt to DIN 53778
Scrubbing cycles:	> 5,000 DH, scrubbing resistant to DIN 53778
Usage:	approx. 150 ml/m ² per coat
GISBAU product code:	M-PL01

Surface preparation:

The surface must be dry, firm, and free of release agents (dust, etc.) Remove all traces of loose plaster, flaking remaining paint and old distemper paint. Prime highly absorbent, sanding and chalking surfaces using *PUFAS Deeply Penetrating Primer – solvent free* or *LH*.

Application:

Apply *PUFAS Rapid Renovation Paint* unthinned using a solvent-resistant roller or a suitable airless spray gun. When using an airless spray gun adjust the paint to spraying consistency using a proprietary thinner (e.g. *aromatic compounds free Reno-Inn Thinner*).

Where the surfaces are highly soiled we recommend you apply a second coat. The first coat must be completely dried before the second coat of paint is applied. Depending on the absorbency of the surface and the ambient temperature the drying time is approx. 2-4 hours. *PUFAS Rapid Renovation Paint* contains solvents and therefore should never be thinned with water.

Do not use if the surface and/or room temperature are below + 5° Celsius! Clean tools using *PUFAS Brush Cleaner R120* or *Soluwash S* immediately after use.

Important information:

Please see the EU Safety Data Sheet for all safety-related data (EU-CLP).

Storage:

Keep containers tightly shut, store in a cool and dry place! Keep away from naked flames and other ignition sources.

Available sizes:

10 l Art.No.: 012602000 EAN: 4007954126028

