

Iso-Plus 3 in 1 Stain Blocker Spray

Iso-Plus 3 in 1 Isolierweiß rapid

Ready-to-use insulating spray for blocking stains on ceilings and walls.

Area of application:

Quickly and permanently isolates stains and water-soluble contaminants, such as:

- Water stains
- nicotine and soot stains
- Fire residues
- Grease and tar stains
- Felt-tip pens
- Graffiti
- Mould stains and discolouration

Prevents subsequent contamination from showing through when wallpapering or painting with emulsion paints.

Properties:

- for sealing off stains on walls and ceilings
- quick-drying – overcoatable after 10 minutes
- opaque white finish

Technical data:

Raw material base: alkyd resin, titanium dioxide, chalk, test gasoline, propellant and additives
 Colour: White
 Density: 0.75 g/cm

Substrate preparation:

Suitable for use on all types of woodchip, emulsion paints, plaster, fillers, concrete and wood, as well as polystyrene*. The surface must be stable and dry. Remove any existing mould thoroughly with *PUFAS Algae and Mould STOP* and, if necessary, treat the surface with *PUFAS Fungi-Plus 3in1*.

Application:

Shake *Iso-Plus 3 in 1 Stain Blocker Spray* vigorously for at least one minute before use (until you can hear the mixing balls hitting the bottom). The insulating spray can then be applied directly to the affected area.

Important information:

Do not use at object and ambient temperatures below +5°C.

Storage

Store containers tightly closed in a cool place, but not exposed to frost. Keep out of reach of children.

Disposal:

Only recycle containers that are completely empty. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of liquid residues as hazardous waste.

Safety



Danger

Extremely flammable aerosol. Container is pressurised: may burst if heated. Harmful to aquatic organisms, with long-term effects. Causes skin irritation. May cause drowsiness and dizziness. Keep out of reach of children. Use only outdoors or in well-ventilated areas. Do not spray on open flames or other sources of ignition. Avoid inhaling vapour/aerosol. Wear protective gloves/eye protection. IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and if easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. If medical advice is needed, have product container or label at hand. Avoid release to the environment. Dispose of contents/container in accordance with local/regional/national regulations. Container is pressurised: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Contains: Naphtha (petroleum), hydrotreated light hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

Item no.:

01960300

500 ml spray bottle



Note:

All information and data in this information sheet correspond to our practical experience and laboratory tests and are based on the current state of technology. However, they can only provide general information and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal liability can be derived from this information. It is the responsibility of the user to check the products for their suitability for the intended use under the respective conditions.