

Solupast D Removing Agent

Use:

Solupast D quickly and reliably removes **1. floor covering residue**, e.g. compact foam residue left after stripping out old coverings **2. adhesive residue** from dispersion and synthetic resin adhesives – e.g. floor covering adhesives, residue from adhesive tape and self-adhesive tiles **3. dried paint/coating stains** – e.g. emulsion paints, synthetic resin and acrylic coatings. Ideal for cleaning soiled tools and stiff natural-bristle brushes.

Technical data:

Raw material base: Dibasic ester, surfactant and auxiliary materials
Density: Approx. 1.1 g/cm³

Instructions for use:

Floor covering and adhesive residue:

Apply Solupast D generously with solvent-resistant brush or roller and, depending on adhesive, allow to work for 15 – 60 minutes. Scrape off dissolved adhesive coat with spatula. Repeat procedure if necessary. Thoroughly wash down surface with water and, where necessary, cleaner and allow to fully dry.

Dried paint/coating stains:

Allow Solupast D to work for approx. 10 – 30 minutes and rub down with cloth to remove stain. Then wash down thoroughly with water.

Cleaning:

Soak stiff natural-bristle brush in Solupast D in glass or metal container. After allowing adequate time to work, rinse out. Smaller metal components shall be placed in and larger metal components wiped over with Solupast D. Then likewise rinse out with water.

Note:

The delayed evaporation of Solupast D allows it to work for long periods without reapplication. Solupast D is a thixotropic gel and can also be applied to vertical surfaces.

Removing agent may attack non-solvent-resistant plastics and mastic asphalt. Prior to use, test surfaces at inconspicuous location for compatibility. Do not use Solupast D on absorbent substrates (e.g. cement screeds). Divide larger areas into sections of max. 0.5 m² for treatment, ensuring adequate ventilation. Allow substrate to fully dry and properly ventilate space before performing subsequent works or installing new floor coverings. Store in cool place in properly sealed containers.

Please consult safety data sheet for safety-relevant data. Up-to-date safety data sheets are available from our website at www.pufas.de/www.decotric.de or from sds@pufas.de/sds@decotric.de.

Storage:

Store in cool, though frost-free environment in properly sealed containers, out of reach of children.

Disposal:

Hand over only fully emptied containers for recycling. Dried material residue may be disposed of as domestic or construction site waste. EWC waste code: 08 04 12.

Item No.	EAN	Container size
120202000	4007954202326	1 ltr



Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.